



## Wuxi LZH Bearing Co., Ltd.



SYR 2.3/4 N Bearing 2D drawings and 3D CAD models

2.75 Inch | 69.85 Millimeter x 2.578 Inch | 65.481 Millimeter x 3.25 Inch | 82.55 Millimeter SKF SYR 2.3/4 N Pillow Block Bearings

Bearing No. SYR 2.3/4 N

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	9.99
EAN	7316577312297
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22215
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row   Heavy Duty   Open End   With Grub Screw
Long Description	2 Bolt Pillow Block; 2-3/4" Bore; 3-1/4" Base to Center Height; Stepped Sleeve Mount; Spherical Roller



## Wuxi LZH Bearing Co., Ltd.

	Bearing; 7-13/16" Minimum Bolt Spacing; 8-7/16" Bolt Spacing Maximum; Relubri
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SYR 2.3/4 N
Weight / LBS	22
d	2.75 Inch   69.85 Millimeter
D	2.578 Inch   65.481 Millimeter
Bolt Spacing Minimum	7.813 Inch   198.44Millimeter
Bolt Spacing Maximum	8.438 Inch   214.325Millimeter
Nominal Bolt Center to Center	8.1 Inch   206.4 Millimeter
B	3.25 Inch   82.55 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
bore diameter:	2.7500 in
bolt center-to-center length:	8-1/8 in
overall length:	10.4375 in
base width:	2-9/16 in
overall height:	6.4375 in
expansion type:	Expansion Bearing (Floating)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard
bore type:	Round



## Wuxi LZH Bearing Co., Ltd.

radial dynamic load capacity:	47500 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	54000 lbf
base to bore centerline:	3.2500 in
maximum rpm:	1600 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Concentric Collar
replacement bearing:	22215